

Pisos vinílicos SPC- Sistema Click – Liston Normal

TECHNICAL SPECIFICATION	TEST STANDARD	TEST LIMITS	DETAILS / TEST RESULT
PRODUCT COMPOSITION			STONE PLASTIC COMPOSITE
DIMENSIONS	-	-	1220 mm x 182 mm x 4 mm + 1mm; with 4 Side Micro bevel
WEAR LAYER	-	-	0.5 mm
PACKING SIZE	-	-	10 Planks Per Box; 2.22 SQM / 23.9 SQ.FT Per Box
WEAR GROUP			GROUP T
SURFACE FINISH	-	-	EMBOSSSED
LOCKING	-	-	CLIC TECHNOLOGY
COLOUR FASTNESS	EN ISO 105-B02	-	Grade Blue wool: 6
REACTION TO FIRE / FIRE RETARDANCY:	EN 13501-1 EN ISO 9239-1 EN ISO 111925-2	-	Bfl-s1
Impact Resistance	NALFA LF-01 ANSI - NALFA - LF 01	-	No cracking or fracturing.
Slip Resistance	AS 4586-2013 Amdt 1-2017	6 < X < 10	R9
Formaldehyde Emission	ASTM D6007-14	P2 = 0.05 PPM	< 0.01 PPM
Soluble Heavy Metal	ASTM F963-16	MAX 10	< 10
Phthalates	EN 14372:2004	MAX 0.01	< 0.01
RoHS	IEC 62321	MAX 5	< 5

ATTESTATION



No. 3N230710.CDWTS38

Test Report / Technical Construction File no. JAT-CE1282-20230705CPR

Attestation's Holder: CHANGZHOU DELAI WOOD CO., LTD.
No. 8-1 Gongqing Village, Henglin Town, Wujin District, Changzhou

Attestation
ECM Mark:



Product: PVC Flooring
Model(s): 1.5mm-8mm

Verification to: Standard:
EN 14041:2018
related to CE Directive(s):
R 305/2011 (Regulation for the Marketing of Construction Products)

This document has been issued in accordance with the European Commission's note of 14 September 2022 ref. Ares (2022) 6342894 concerning voluntary certifications with a non-notified procedure as it does not fall within the scope of Ente Certificazione Macchine notification under harmonised Union and for products intended for third countries outside the EU market.

The manufacturer has voluntarily decided to submit its documents concerning the above-mentioned product for verification. Ente Certificazione Macchine confirms that the documentation made available and immediately returned to it, as containing sensitive data, meets the essential requirements of the above-mentioned directives. The verification activity carried out exclusively concerned the technical documentation and no verification was carried out on the product. This document cannot replace the EC Declaration of Conformity. The above conformity mark can be affixed to the technical documentation in accordance with the ECM regulation on its issue and use, published on the website www.entecerma.it

Issuance date: 10 July 2023**Expiry date: 09 July 2028**

For online check:



Approver
Ente Certificazione Macchine
Legal Representative
Luca Bedonni



SCS Global Services does hereby certify that an independent assessment has been conducted on behalf of:

Changzhou Youkang Decoration Materials Co., Ltd.

No.12 Weixi Road, Cuiqiao Henglin Town, Changzhou, China

For the following product(s):

Vinyl Tile:

Stone Plastic Composite (SPC) Flooring (*Maximum thickness: 9.5mm*)

The product(s) meet(s) all of the necessary qualifications to be certified for the following claim(s):

FloorScore®

Indoor Air Quality Certified to SCS-105 Version 4.2 – 2023

Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350), effective April 1, 2017, for the school classroom and private office parameters when modeled as Flooring.

Measured Concentration of Total Volatile Organic Compounds (TVOC): Less than/equal to 0.5 mg/m3 (in compliance with CDPH/EHLB Standard Method v1.2-2017)

Registration # SCS-FS-04850

Valid from: March 01, 2025 to February 28, 2026

SCS Global Services is currently the only certification body approved by the Resilient Floor Covering Institute (RFCI) to provide FloorScore® product certification; certified products are only listed on the SCS Green Products Guide, <http://www.scsglobalservices.com/certified-green-products-guide>.



ANSI National Accreditation Board
ACCREDITED
ISO/IEC 17065
PRODUCT CERTIFICATION
BODY



A handwritten signature in black ink.

Diana Kirsanova Phillips, Chief Assurance Officer,
SCS Global Services